

## Badu Professional 4-11



## Design

- Smooth runnin
- ow-wear materials
- Sc ews on the suction and pressure sides
- Be low-type mechanical seal on a plastic protector
- Self-priming pump (assembly max. 2 m. above or max. 3 m. below the water level)

# **Field of Application**

The BADU Professional self-priming pool pump is a real all-rounder for private or public pool and pond units. Due to the flexible connection options and the large strainer tank, it is perfect for:above ground pools, partially submerged pools, built-in pools, swimming ponds fish ponds.

## Badu Profession 18-36







## **Material Used**

Pump casing	PP GF 30
Housing cover	PP TV 30
Impeller	PA 66 GF 30/PP GF 30/PPE GF 30
Strainer basket	PP
Lid	PC, transparent/PP GF 30
Union with Glue sockets	PVC-U
Mechanical seal	carbon/ceramic/NBR
Motor shaft	stainless steel
Screws	galvanised steel/stainless steel

5	Р	=(0	К	- B	ΑĐ	U	Р	RU	9)=	E.	5	10	N	٩L

Badu Professional 4-11				
MODEL	DESCRIPTION	PIPING	FLOWRATE*	
BADU Professional 4	0.25 HP/220V	1.5"	4 m <sup>3</sup> /Hr	
BADU Professional 4-380	0.25 HP/380V	1.5"	4 m3/Hr	
BADU Professional 6	0.33 HP/220V	1.5"	6 m3/Hr	
BADU Professional 6-380	0.33 HP/380V	1.5"	6 m3/Hr	
BADU Professional 8	0.5 HP/220V	1.5"	8 m3/Hr	
BADU Professional 8-380	0.5 HP/38V	1.5"	8 m3/Hr	
BADU Professional 11	0.75 HP/220V	1.5"	11 m3/Hr	
BADU Professional 11-380	0.75 HP/380V	1.5"	11 m3/Hr	

Badu Professional 18-36						
MODEL	DESCRIPTION	PIPING	FLOWRATE*			
BADU Professional 18	1 HP/220V	2"	18 m <sup>3</sup> /Hr			
BADU Professional 18-380	1 HP/380V	2"	18 m3/Hr			
BADU Professional 22	1.5 HP/220V	2"	22 m3/Hr			
BADU Professional 22-380	1.5 HP/380V	2"	22 m3/Hr			
BADU Professional 27	1.75 HP/220V	2"	27 m3/Hr			
BADU Professional 27-380	1.75 HP/38V	2"	27 m3/Hr			
BADU Professional 30	2 HP/220V	2"	30 m3/Hr			

2"

2"

2"

\*calculated at head 8m

30 m3/Hr

36 m3/Hr

36 m3/Hr

BADU Professional 30-380

BADU Professional 36-380

**BADU Professional 36** 

2 HP/380V

3 HP/380V

3 HP/380V