

## Underground Filtration System

Model	Description	Piping	Flowrate	Dimension
		(mm)	(m <sup>3</sup> /h)	(mm)
<b>A-605</b>	<b>Underground Filtration System with Salt Chlorinator and Massage Pump</b> Include: - Fiberglass Sand Filter Model. QS650, Side Mount 1.5" (1 set) - Filtration Pump Model. AU150, 1.5HP, 1.1KW/220V, 1.5" (1 set) - Massage Pump Model. AU200, 2.0HP, 1.5KW/220V, 1.5" (1 set) - Submersible Pump (1 set) - Salt Chlorinator Model. RCL-35, Output 35grams/Hr. (1 set) - Electronic Box (2 sets)	50	18	1430x1330x1048
<b>A-904</b>	<b>Underground Filtration System with Salt Chlorinator and Massage Pump</b> Include: - Fiberglass Sand Filter Model. QS900, Side Mount 2" (1 set) - Filtration Pump Model. AK300, 3.0HP, 2.2KW/220V, 2" (1 set) - Massage Pump Model. AU200, 2.0HP, 1.5KW/220V, 1.5" (1 set) - Submersible Pump (1 set) - Salt Chlorinator Model. RCL-35, Output 35grams/Hr. (1 set) - Electronic Box (2 sets)	63	32	1720x1670x1364

