

Bobbin – wound Fiberglass Filter



Bobbin-wound Fiberglass top mount filter is made of high quality fiberglass and resin, the fiberglass winding structure makes the sand filter more stronger, there's UV-resistant on the surface, the whole filter has good resistance to chemical and sun protection. This collection is the first choice for water treatment equipment at swimming pools, hot springs, spa, aquariums, water parks & etc.

- UV-resistant surface finished.
- Equipped with a 1.5" – 2" six-position multiport valve
- Universal standard of union connection provided
- Max. Operating pressure 36 psi (2.5bar)
- Max. Temperature 43 C (109 F)
- Suggested size of media 0.5 – 0.8 mm.

Model	Ø (mm)	Max. Flow Rate		Filter area m ²	Connections		Sand Kg.
		m ³ /h	lpm		inch		
PB550T	530	11.10	185	0.22	1.5"		85
PB650T	640	15.60	260	0.32	1.5"		145
PB700T	700	20.16	336	0.41	2"		215
PB750T	750	23.00	383	0.44	2"		230
PB800T	800	24.90	415	0.50	2"		355
PB900T	900	31.20	520	0.64	2"		470

Dimension (mm)

Model	A	B	C	D	E	F
PB550T	830	720	660	235	530	390
PB650T	980	820	760	300	640	500
PB700T	1083	930	870	390	700	500
PB750T	1150	980	900	430	750	710
PB800T	1200	1020	950	425	800	710
PB900T	1310	1160	1080	480	900	710

